

What is claimed is:

1. A modular mezzanine connector system, comprising:
 - (a) a plug assembly, comprising
 - (a₁) a first common base comprising a plurality of fusible
5 elements which are each disposed within a pocket defined within the first common base;
 - (a₂) a plug contact assembly mounted within the plug
assembly comprising a plurality of plug contacts, each plug contact comprising an end
which is secured to one of the fusible elements within one of the pockets of the first
common base;
 - 10 (a₃) a plug cover coupled to the first common base;
 - (b) a receptacle assembly that mates with the plug assembly,
comprising
 - (b₁) a second common base comprising a plurality of
fusible elements which are each disposed within a pocket disposed within the second
15 common base and wherein the first common base and the second common base are
substantially identical;
 - (b₂) a receptacle contact assembly mounted within the
receptacle assembly comprising a plurality of receptacle contacts, each receptacle contact
comprising an end which is secured to one of the fusible elements within one of the
20 pockets of the second common base;
 - (b₃) a receptacle cover that is coupled to the second
common base and that mates with the plug cover.
2. The modular mezzanine connector system of claim 1, wherein the
plug assembly further comprises a spacer mounted between the plug cover and the first
25 common base.
3. The modular mezzanine connector system of claim 1, wherein the
receptacle assembly further comprises a spacer mounted between the receptacle cover and
the second common base.

09919321.073101

4. The modular mezzanine connector system of claim 1, wherein the plug assembly further comprises a spacer mounted between the plug cover and the first common base and the receptacle assembly further comprises a spacer mounted between the receptacle cover and the second common base.

5 5. The modular mezzanine connector system of claim 1, wherein the pockets of the first and the second common base are disposed in an interstitial diamond configuration.

6. The modular mezzanine connector system of claim 1, wherein the pockets of the first and the second common base are disposed in an interstitial diamond
10 configuration and the first and the second common base further comprise a recess disposed above each of the pockets through which a contact can be inserted.

7. The modular mezzanine connector system of claim 1, wherein the plurality of plug and receptacle contacts are disposed in an in-line stripline configuration.

8. The modular mezzanine connector system of claim 1, wherein the
15 plurality of plug contacts and receptacle contacts are disposed in a stripline I-Beam configuration.

9. The modular mezzanine connector system of claim 1, further comprising an adaptor which is mated to the plug cover and the receptacle cover.

20 10. A method of making a modular mezzanine connector system to a desired stack height, comprising:
inserting a plurality of plug contacts into a first common base;
coupling a plug cover to the first common base and if needed to meet the desired stack height attaching a spacer between the plug base and the plug cover;
25 inserting a plurality of receptacle contacts into a second common base;
base;

09919321.073101
TOTAL 225660

receptacle cover comprises inserting the receptacle cover into an interior of the plug cover in an interference fit.

18. The method of claim 10, wherein coupling the plug cover to the receptacle cover comprises inserting the plurality of plug contacts through slots in the
5 receptacle cover and into contact with a corresponding receptacle contact.

19. A modular mezzanine connector system, comprising:
a plug assembly and a receptacle assembly that mates with the plug assembly, the plug assembly and the receptacle assembly each comprising a base which comprises
10 a plurality of recesses;
a plurality of diamond pockets disposed in an interstitial diamond configuration and there being a pocket beneath each recess so that a contact can extend through one of the recesses and into one of the pockets;
the plurality of recesses being substantially rectangular in shape so
15 that a contact extending through the recess and into the diamond pocket can receive a fusible element around a periphery of a portion of the contact extending into the pocket.

20. The modular mezzanine connector system of claim 19, further comprising a plug cover coupled to the base of the plug assembly and a receptacle cover
20 coupled to the base of the receptacle assembly.

21. The modular mezzanine connector system of claim 19, wherein the plug assembly further comprises a plurality of plug contacts disposed in an in-line stripline configuration and the receptacle assembly further comprises a plurality of receptacle contacts disposed in an in-line stripline configuration.

22. The modular mezzanine connector system of claim 19, wherein the
25 plug assembly further comprises a plurality of plug contacts disposed in a stripline I-Beam configuration and the receptacle assembly further comprises a plurality of receptacle

09019321.073101
TOTEST

contacts disposed in a stripline I-Beam configuration.

[illegible]